

# SWIWIN SW240Pro



## Technical specifications



## SWIWIN SW240Pro List of engine accessories

serial number	name	Picture specification	quantity
1	Engine body		1 set
2	ECU (V4)		one
3	GSU		one
4	Fixing frame		one
5	Power cord plug		one
6	Signal wire plug		one
7	Switch valve		one



8	Oil filtration		one
9	Tubing	 4*2.5mm和6*4mm	2 meters each

## Technical parameter

model	SW240Pro
Thrust	24kg
Diameter (mm)	115.5mm
Length (mm)	278.5mm
weight	1740g
ECU weight	353g
usage temperature	-40°C~50°C
supply voltage	3S Lipo battery
starting system	One-button electronic start
Rpm Range	38000-118000
Exhaust Temperature	750°C
Fuel Consumption	780g/min
fuel	kerosene
lube oil	3%~5%
Maintenance Interval	25H

## Engine start parameters

Pump Voltage	0.5-1.2V
RPM Start Up Ramp	100%
Pump Start Up Ramp	3
Glow Plug	5-7V
Valve	40
Ignition RPM	3000
Preheat RPM	5000
RPM Off Starter	20000

## Engine operating parameters

RPM ACC	25
RPM DEC	25
Max RPM	118000
Idle RPM	38000
Minimum speed	28000
Max Temp	1000
Low Volt	10V
Restart	close
Restart Glow Plug	Consistent with the voltage of the burner
Pump Limit	10V
Idle Stable	8

## Engine cooling parameters

cool

5000rpm

---


## Starting motor parameters

Pop-up time	0.5S
Ejection voltage	4V
Run Voltage	4V
RPM Stable	50

---

Note: All data are measured at standard air pressure.

## System connection diagram





### Product dimension diagram

